

ASPHALT RELEASE AGENT

ANTI ADHESION COATING

TRANSPARENT-LONG LASTING
EASY TO REMOVE

A long lasting, transparent anti-adhesion barrier that protects any smooth surface during asphalt and tar operations, mortaring or plastering operations. Exclusive additives insure high density of film, thus giving complete protection without bleeding or spotting. Ideal for use to coat truck bodies and beds for easy removal of asphalt, tar, concrete etc.

DIRECTIONS:

Remove old residues. Spray a thin coat evenly over the clean dry surface using a pressure sprayer. Allow to dry, and use as normal.

May be safely used on: Truck bodies, Door Bucks, Exposed Equipment Window Frames, Wood Trim, Risers and Stringers, Any smooth surface requiring protection.

NET CONTENT: 5 US GALLONS

CAUTION: KEEP OUT OF REACH OF CHILDREN
Industrial & Institutional Use Only

WARNING:

Combustible liquid.

HEALTH HAZARDS:

May be fatal if swallowed and enters airways.

- * Keep away from heat, sparks, and flame.
- * When burned the product produces carbon monoxide and other asphyxiants during combustion.
- * Avoid breathing vapor. Harmful if inhaled and may cause delayed lung injury.
- * Aspiration hazard if swallowed - can enter lungs and cause damage.
- * Use ventilation adequate to keep vapor below recommended exposure limits.
- * Avoid contact with eyes, skin and clothing. Material splashed into the eyes will irritate tissues. Gently flush material from eyes with clean water.
- * Unprotected exposure to this product will cause skin dryness.
- * Remove product soaked clothing and wash with mild soap. Wash thoroughly after handling.
- * As with any petroleum product, avoid mixing this product with strong oxidizers.
- * This product is not listed on the NTP, IARC, OSHA, or ACGIH lists of suspected or confirmed carcinogens.
- * This product may be toxic to fish but will be toxic to birds and wildlife through ingestion during pelage cleaning.
- * This product is readily biodegradable in the presence of air and sunlight.
- * Spilled material is slippery and may cause falls.

Contains: Petroleum Distillates CAS #8052 - 41 - 3
166193

CAUTION
KEEP OUT OF REACH OF
CHILDREN

REORDER FROM:



REORDER FROM:

ACS SOLUTIONS
P.O BOX 9556 CORAL SPRINGS, FL 33065
877-813-6427